

BABAC®

TRACTION PRODUCTS

BABAC® Forestry and Heavy Equipment Tire Chains are 100% American Made and Hand Assembled for Optimum Quality Control.

BABAC® tire chains are built from 10B21 through hardened boron alloy steel, with a uniform hardness and tensile strength throughout. Extensive tests and field experience have shown that BABAC® tire chains wear longer, more uniformly, and without breakage associated with case hardened products.

BABAC® offers a full line of standard tire chain patterns for skidder, forwarder, harvester, tractor, and heavy equipment applications. BABAC® has computer design capability and specializes in custom tire chain applications and odd tire sizes.

RING TIRE CHAINS

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)	1" (25 mm)
------------------	-----------------	-----------------	-----------------	---------------

All BABAC® models feature alloy lugs that, unlike most other chains, are butt and wrap welded for unsurpassed strength and durability. Our slanted half links take out pre-load as the chain goes over the tire. This reduces friction and wear, and allows for free tag chain movement. It is a standard feature on all BABAC® ring chains.



BSR STANDARD RING®

Self-cleaning design.

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)
------------------	-----------------	-----------------

BABAC® Ring chains provide excellent traction for operating in mud or snow.



BS5R 5 LINK RING®

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)
------------------	-----------------	-----------------

BSMR MULTI RING®

Offers a smooth ride.

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)	1" (25 mm)
------------------	-----------------	-----------------	-----------------	---------------

BDMR DOUBLE MULTI RING®

Superior coverage for wider tires.

5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)
-----------------	-----------------	-----------------



9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)
-------------------------	------------------------	------------------------	------------------------

DIAMOND® STUD CHAINS



STANDARD U-FORM® STUDS

Diamond® chains feature BABAC®'s world-renowned U-Form® stud design. U-Form® studs are welded on the flat (square) side of the link remaining upright for better wear and superior traction. These studs do not lay down like traditional studded chains, improving traction over rock, frozen/wet wood, ice or ledge. Studs are formed wire with finished ends.



OPTIONAL ROUGH CUT STUDS

An economical alternative to our standard U-Form® studs, our Rough Cut studs are hydraulically sheared pieces of 10B21 Boron Alloy chain, heat treated to the same specifications as our standard U-Form® studs.

BSS SINGLE DIAMOND®

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)
-------------------------	------------------------	------------------------	------------------------



BDS DOUBLE DIAMOND®

9/16" (14 mm)	5/8" (16 mm)	3/4" (19 mm)	7/8" (22 mm)
-------------------------	------------------------	------------------------	------------------------



BTS TRIPLE DIAMOND®

5/8" (16 mm)	3/4" (19 mm)
------------------------	------------------------



BABAC®'s unique U-Form® stud chains have the best wear characteristics of any chain in the world.

BFP FORESTRY PROTECTION

5/8" (16 mm)	3/4" (19 mm)
------------------------	------------------------



BTSE EURO STYLE™

9/16" (14 mm)	5/8" (16 mm)
-------------------------	------------------------

